

## MARINE BATTERY CABLE

### 105°C DRY 75°C WET 600V TINNED COPPER



One of the primary concerns of professional technicians is cable flexibility. Marine applications are characteristically in enclosed areas with sharp turns. The less flexible the cable, the more difficult the job will be. The two factors effecting a cable's softness are its stranding and its insulation. Pacer's UL listed marine battery cable is made of type III rope stranded tinned copper and is insulated with a pliable yet durable compound. It maintains key physical and electrical resistance properties. Pacer Marine's battery cable's flexibility and consistent quality has made it the preferred choice among hundreds of marine OEM's.

Pacer stocks a full line of gauges and colors. Put-up sizes are 50, 100 and 500 foot put-ups.

#### FEATURES:

- Finely stranded tinned copper conductor (Type III)
- Color coded PVC insulation (See chart for specifics per gauge)
- Temperature Range: -20°C to 105°C
- Voltage Rating: 600V
- Resistant To: Acid, Alkalis, Abrasion, Flame, Gasoline, Oil, Ozone, Moisture, Fungus
- Applications: Connecting battery or generator to switch, starter or ground Windlass, Inverter or any high amperage equipment

#### COMPLIANCES:

UL Standard 1426 (BC-5W2)  
 AWM 1232/1283 (6-2 AWG)  
 AWM 1232/1284 (1 AWG - 4/0)  
 CSA: TEW  
 ABYC: E-8.14, E-9.14  
 Coast Guard: 33 CFR part 183 Subpart I  
 NMMA

PART NUMBER (A)	AWG	COND. STRAND THICKNESS	NOM. INSULATION	NOMINAL O.D.	STANDARD PUT-UPS	APPRX. SHIP LBS./M
WUL6	6	266/.0100	.060	.340	C, TL, D	136
WUL4	4	420/.0100	.060	.398	L, C, TL, D	189
WUL2	2	665/.0100	.060	.464	L, C, TL, D	292
WUL1	1	836/.0100	.080	.567	L, C, TL, D	305
WUL1/0	0	1064/.0100	.080	.621	L, C, TL, D	450
WUL2/0	00	1330/.0100	.080	.653	L, C, TL, D	551
WUL4/0	0000	2109/.0100	.080	.785	L, C, TL, D	820

SEE TECHNICAL DATA PAGE 61 FOR CIRCULAR MIL AREA OF CONDUCTORS.

COLOR	COLOR ABBR. (B)	6	4	2	1	1/0	2/0	4/0	PUT-UP DESIGNATION (C)	QTY.
BLACK	BK								-L	50
RED	RD								-C	100
ORANGE	OR								-TL	250
YELLOW	YL								-D	500
GREEN	GN									
WHITE	WH									

#### ORDERING INFORMATION

Order by standard put-up size.

Combine Part Number (A) with Color Abbreviation (B) and Put-up Designation (C)

EXAMPLE: 2/0 AWG Black, 250 Feet = WUL2/OBK-TL