



## SKINTOP® II LIQUID TIGHT CONNECTORS

SKINTOP® II Liquid tight, non-metallic strain relief connectors are an easy method of sealing out moisture from electrical boxes or between bulkheads. SKINTOP® II connectors meet the most stringent demands of safety and operational reliability. The internal ratchet mechanism allows the cap to be tightened without twisting the cord as it compresses. An integrated locking system prevents the cap from loosening even when subjected to severe vibration. Used both as a strain relief and liquid tight connector, SKINTOP® II is an all in one connector for panels, switches, control boxes, submersible pumps, and many other applications.

### FEATURES:

- International approvals, UL, CSA, VDE, SEV
- NPT Threads and PG Threads
- Continuous operating temperature range of -20°C to 80°C.
- Protection up to 70 PSI
- Resistant to common fluids and solvents
- Material: Polyamide - flame retardant and self-extinguishing nylon with neoprene bushing
- Seal: IP 68 (International Protection highest rating, comparable to NEMA 6)
- Available in gray

### NPT (Locking Nuts Sold Separately)

PART NUMBER	DIAMETER RANGE	MOUNTING HOLE	MAX. OVERALL LENGTH	THREAD LENGTH
BSLC-3/8	.157-.314	.675	1.692	.563
BSLC-1/2	.236-.476	.825	1.734	.563
BSLC-3/4	.545-.709	1.050	1.969	.563
BSLC-1	.708-.984	1.303	2.283	.563

### ORDERING INFORMATION:

Order by the piece. Locking Nuts sold separately.

### PG (Locking Nuts Included)

PART NUMBER	DIAMETER RANGE	MOUNTING HOLE	MAX. OVERALL LENGTH	THREAD LENGTH
BSLC-36	.866 - 1.259	1.85	2.519	.512
BSLC-42	1.259 - 1.496	2.126	2.638	.512
BSLC-48	1.456 - 1.732	2.335	2.717	.551

## LOCKING NUTS

- Made from 6/6 gray nylon
- Meets UL flammability 94 V-2
- Maximum temperature rating 125°C

PART NUMBER	THREAD SIZE
BSLN-3/8	3/8"
BSLN-1/2	1/2"
BSLN-3/4	3/4"
BSLN-1	1"

### ORDERING INFORMATION:

Order by the piece.




## CABLECLAMS

- Waterproof co-axial installation without removing connectors
- Save the expense of removing and replacing connectors
- Avoid poor connections from removing factory connectors


### SPECIFICATIONS:

Body Material Acetal  
 Seal Material UV-Stabilized Buna-N-Rubber  
 Screws Stainless Steel


PART NUMBER	DESCRIPTION
BCLM-1001	CableClam 0.625" Connector Opening
BCLM-1002	CableClam 0.825" Connector Opening
BCLM-1003	CableClam 1.385" Connector Opening



1001



1002



1003