



TINNED PLATED "CLOSED END" LUGS

General purpose seamless electrical terminals. Made from 100% pure electrolytic copper, fully annealed to prevent cracking while being crimped and while in service. Tinned plated for optimum corrosion resistance. All lugs have a flared "bell" shaped entry to facilitate wire insertion. Pacer's closed end lugs are uniquely made so that there is no exposed seam on the outside of the terminal.

FEATURES:

- Tinned plated, E.T.P. (Electrolytic Tough Pitch) CDA-110, ASTM-B-152 copper, rated at 100% conductivity
- UL and CSA Approved
- No exposed seams

WIRE RANGE	STUD SIZE	PART NUMBER	LENGTH	WIDTH	CLEARANCE	STANDARD PACKAGE
#8 AWG	#10	TAE8-10R-T	1.187	.438	.344	25, 50, 100, 500
	1/4"	TAE8-14R-T	1.187	.438	.344	25, 50, 100, 500
	5/16"	TAE8-56R-T	1.187	.438	.344	25, 50, 100, 500
	3/8"	TAE8-38R-T	1.344	.609	.406	25, 50, 100, 500
	1/2"	TAE8-12R-T	1.484	.766	.469	25, 50, 100, 500
# 6 AWG	#10	TAE6-10R-T	1.266	.438	.344	25, 50, 100, 500
	1/4"	TAE6-14R-T	1.266	.438	.344	25, 50, 100, 500
	5/16"	TAE6-56R-T	1.266	.438	.344	25, 50, 100, 500
	3/8"	TAE6-38R-T	1.406	.609	.406	25, 50, 100, 500
	1/2"	TAE6-12R-T	1.547	.766	.469	25, 50, 100, 500
# 4 AWG	#10	TAE4-10R-T	1.500	.531	.406	25, 50, 100, 500
	1/4"	TAE4-14R-T	1.500	.531	.406	25, 50, 100, 500
	5/16"	TAE4-56R-T	1.500	.531	.406	25, 50, 100, 500
	3/8"	TAE4-38R-T	1.500	.531	.406	25, 50, 100, 500
	1/2"	TAE4-12R-T	1.688	.766	.469	25, 50, 100, 500
# 2 AWG	1/4"	TAE2-14R-T	1.625	.609	.406	10, 25, 50, 100
	5/16"	TAE2-56R-T	1.625	.609	.406	10, 25, 50, 100
	3/8"	TAE2-38R-T	1.625	.609	.406	10, 25, 50, 100
	1/2"	TAE2-12R-T	1.750	.766	.469	10, 25, 50, 100
# 1 AWG	1/4"	TAE1-14R-T	1.719	.692	.406	10, 25, 50, 100
	5/16"	TAE1-56R-T	1.719	.692	.406	10, 25, 50, 100
	3/8"	TAE1-38R-T	1.719	.692	.406	10, 25, 50, 100
	1/2"	TAE1-12R-T	1.719	.692	.469	10, 25, 50, 100
# 1/0 AWG	1/4"	TAE1/0-14R-T	1.844	.734	.406	10, 25, 50, 100
	5/16"	TAE1/0-56R-T	1.844	.734	.406	10, 25, 50, 100
	3/8"	TAE1/0-38R-T	1.844	.734	.406	10, 25, 50, 100
	1/2"	TAE1/0-12R-T	1.844	.734	.469	10, 25, 50, 100
# 2/0 AWG	1/4"	TAE2/0-14R-T	2.063	.813	.500	10, 25, 50, 100
	5/16"	TAE2/0-56R-T	2.063	.813	.500	10, 25, 50, 100
	3/8"	TAE2/0-38R-T	2.063	.813	.500	10, 25, 50, 100
	1/2"	TAE2/0-12R-T	2.063	.813	.500	10, 25, 50, 100
# 3/0 AWG	1/4"	TAE3/0-14R-T	2.172	.906	.500	10, 25, 50, 100
	5/16"	TAE3/0-56R-T	2.172	.906	.500	10, 25, 50, 100
	3/8"	TAE3/0-38R-T	2.172	.906	.500	10, 25, 50, 10
	1/2"	TAE3/0-12R-T	2.172	.906	.500	10, 25, 50, 100
# 4/0 AWG	1/4"	TAE4/0-14R-T	2.344	.984	.547	10, 25, 50, 100
	5/16"	TAE4/0-56R-T	2.344	.984	.547	10, 25, 50, 100
	3/8"	TAE4/0-38R-T	2.344	.984	.547	10, 25, 50, 100
	1/2"	TAE4/0-12R-T	2.344	.984	.547	10, 25, 50, 100

TERMINALS
& LUGS

Heavy Duty Starter/Battery Lugs with longer barrels and heavier wall thickness are available upon request.

ORDERING INFORMATION:

Order by standard package.

BRAZED SEAM TINNED BATTERY LUGS

Made from pure electrolytic copper for high conductivity and electro-plated with tin for maximum corrosion protection. Wire barrels are silver alloy brazed, allowing the lug to be crimped anywhere, even on the seam, without splitting. The inside of the barrel is serrated with "V" grooves, which when crimped, grip the wire adding to the holding power. These lugs are very sturdy and durable even in the most demanding conditions.



NON-INSULATED

FEATURES:


- Tinned plated, E.T.P. (Electrolytic Tough Pitch) CDA-110, ASTM-B-152 copper, rated at 100% conductivity
- UL and CSA Approved
- Silver Alloy Brazed Seam.



NYLON INSULATED



Butt Splices



Ring Lugs

BUTT SPLICES

WIRE RANGE	PART NUMBER NON-INS.	PART NUMBER NYLON INS.	INS. COLOR	L NON-INS.	L INSULATED	STANDARD PACKAGE
#8 AWG	TBS8	TBSN8	RED	.77	1.45	25, 50, 100, 500
#6 AWG	TBS6	TBSN6	BLUE	1.02	1.86	25, 50, 100, 500
#4 AWG	TBS4	TBSN4	YELLOW	1.20	2.03	25, 50, 100, 500
#2 AWG	TBS2			1.37		10, 25, 50, 100
#1/0	TBS1/0			1.52		10, 25, 50, 100
#2/0	TBS2/0			1.58		10, 25, 50, 100
#4/0	TBS4/0			1.58		10, 25, 50, 100

RING LUGS

WIRE RANGE	STUD SIZE	NON INS.	NYLON INS.	INS. COLOR	L NON-INS	E NON-INS	C	W	STANDARD PACKAGE
#8 AWG	#10	TL8-10R	TLNF8-10R	RED	.960	.720	.388	.374	25, 50, 100, 500
	1/4"	TL8-14R	TLNF8-14R	RED	.960	.720	.388	.374	25, 50, 100, 500
	5/16"	TL8-56R	TLNF8-56R	RED	1.007	.720	.388	.374	25, 50, 100, 500
	3/8"	TL8-38R	TLNF8-38R	RED	1.136	.785	.453	.583	25, 50, 100, 500
	1/2"	TL8-12R	TLNF8-12R	RED	1.432	.968	.636	.810	25, 50, 100, 500
# 6 AWG	#10	TL6-10R	TLNF6-10R	BLUE	1.215	.896	.511	.480	25, 50, 100, 500
	1/4"	TL6-14R	TLNF6-14R	BLUE	1.215	.896	.511	.480	25, 50, 100, 500
	5/16"	TL6-56R	TLNF6-56R	BLUE	1.215	.896	.511	.480	25, 50, 100, 500
	3/8"	TL6-38R	TLNF6-38R	BLUE	1.296	.896	.511	.643	25, 50, 100, 500
	1/2"	TL6-12R	TLNF6-12R	BLUE	1.479	.988	.603	.825	25, 50, 100, 500
# 4 AWG	#10	TL4-10R	TLNF4-10R	YELLOW	1.288	.994	.547	.475	25, 50, 100, 500
	1/4"	TL4-14R	TLNF4-14R	YELLOW	1.288	.994	.547	.475	25, 50, 100, 500
	5/16"	TL4-56R	TLNF4-56R	YELLOW	1.288	.994	.547	.475	25, 50, 100, 500
	3/8"	TL4-38R	TLNF4-38R	YELLOW	1.385	.994	.547	.665	25, 50, 100, 500
	1/2"	TL4-12R	TLNF4-12R	YELLOW	1.385	.994	.547	.665	25, 50, 100, 500
# 2 AWG	1/4"	TL2-14R	-	-	1.578	1.218	.703	.630	10, 25, 50, 100
	5/16"	TL2-56R	-	-	1.578	1.218	.703	.630	10, 25, 50, 100
	3/8"	TL2-38R	-	-	1.578	1.218	.703	.630	10, 25, 50, 100
	1/2"	TL2-12R	-	-	1.695	1.218	.703	.864	10, 25, 50, 100
	# 1 AWG	1/4"	TL1-14R	-	-	1.840	-	-	.710
5/16"		TL1-56R	-	-	1.840	-	-	.710	10, 25, 50, 100
3/8"		TL1-38R	-	-	1.930	-	-	.710	10, 25, 50, 100
1/2"		TL1-12R	-	-	1.930	-	-	.880	10, 25, 50, 100
# 1/0		1/4"	TL1/0-14R	-	-	1.949	-	-	.820
	5/16"	TL1/0-56R	-	-	1.949	-	-	.820	10, 25, 50, 100
	3/8"	TL1/0-38R	-	-	1.949	-	-	.820	10, 25, 50, 100
	1/2"	TL1/0-12R	-	-	1.980	-	-	.864	10, 25, 50, 100
	# 2/0	1/4"	TL2/0-14R	-	-	2.180	-	-	.928
5/16"		TL2/0-56R	-	-	2.180	-	-	.928	10, 25, 50, 100
3/8"		TL2/0-38R	-	-	2.180	-	-	.928	10, 25, 50, 100
1/2"		TL2/0-12R	-	-	2.180	-	-	.928	10, 25, 50, 100
# 3/0		1/4"	TL3/0-14R	-	-	2.180	-	-	1.047
	5/16"	TL3/0-56R	-	-	2.180	-	-	1.047	10, 25, 50, 100
	3/8"	TL3/0-38R	-	-	2.180	-	-	1.047	10, 25, 50, 100
	1/2"	TL3/0-12R	-	-	2.180	-	-	1.047	10, 25, 50, 100
	# 4/0	1/4"	TL4/0-14R	-	-	2.242	-	-	1.115
5/16"		TL4/0-56R	-	-	2.242	-	-	1.115	10, 25, 50, 100
3/8"		TL4/0-38R	-	-	2.242	-	-	1.115	10, 25, 50, 100
1/2"		TL4/0-12R	-	-	2.242	-	-	1.115	10, 25, 50, 100

ORDERING INFORMATION:

Order by standard package.